(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



A CONTRACTOR REPORT OF THE CONTRACTOR CONTRA

(43) International Publication Date 30 September 2004 (30.09.2004)

(10) International Publication Number WO 2004/084295 A1

(51) International Patent Classification7:

H01L 21/66

(21) International Application Number:

PCT/KR2004/000559

- (22) International Filing Date: 16 March 2004 (16.03.2004)
- (25) Filing Language:


(26) Publication Language:

English

(30) Priority Data:

- 10-2003-0016634 17 March 2003 (17.03.2003) KR
- (71) Applicant (for all designated States except US): PH-ICOM CORPORATION [KR/KR]; 60-29 Gasan-dong, Kumchon-gu, Seoul 153-801 (KR).
- (71) Applicant and
- (72) Inventor: LEE, Oug-Ki [KR/KR]; A/12 Green Villa, 1-5, Hang-dong, Guro-gu, Seoul 152-140 (KR).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): LEE, Jung-Hoon

- (74) Agent: KIM, Inhan; 5th Floor, Daerim Bldg., 1695-4 Seocho-dong, Seocho-gu, Seoul 137-883 (KR).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AB, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, BC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).



probe comprises a body part bent at the middle thereof so that the body part is elastically tensioned or compressed when a tension force or a compression force is applied to the body part at the upper and lower ends thereof, a connection part integrally formed with the lower end of the body part, the connection part being fixed to a substrate, and a tip part integrally formed with the upper end of the body part, the tip part contacting a pad of an element.